



Product Service

CERTIFICATE

No. Z2 052109 0018 Rev. 00

Holder of Certificate: **Aktiv Ude**
Hjerminde Byvej 18
8850 Bjerringbro
DENMARK

Certification Mark:



Product: **Swings**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713207261-1

Valid until: 2026-02-24

Date, 2021-03-26

(Jens Biesenack)

CERTIFICATE

No. Z2 052109 0018 Rev. 00

Model(s): 004.03 (nest swing), 004.03 (2 seats), 004.402, 004.412, 004.413, 004.414, 004.416, 004.417 (nest swing), 004.417 (2 seats)

Parameters:

Seats used by R&T for the swing frame:
Art. -No.: 50 (1256 10), 0150, 0151, 200 (1265),
1256 00, 011202, 011002, 500 (1264U),
501 (1264U black)

Swing frames:

004.03 (nest swing & 2 seat)
double swing frame with A-posts
Connection: by screws
Material: robinia with a diameter of 150 - 180 mm
Length: 4.00 m
Width: 2.20 m
Height: 2.45 m
Safety zone: 8.00 x 4.00 m

004.402
double swing frame with A-posts,
Connection: at the ends with steel fittings
Material: robinia with a diameter of 150 - 180 mm
Length: 4.00 m
Height: 2.50 m
Safety zone: 8.00 x 4.25 m

004.412
freestanding wooden posts with concrete foundation
Material: robinia with a diameter of 150 - 180 mm
Length: 4.00 m
Width: 2.25 m
Height: 2.10 m
Safety zone: 7.00 x 2.60 m

004.413
more bays swing frame with A-posts
Connection: with steel fittings
Material: robinia with a diameter of 150 - 180 mm
Length: 6.00 m
Height: 2.50 m
Safety zone: 8.00 x 7.75 m

004.414
double swing frame with A-posts for a single point swing
Connection: at the ends with steel fittings
Material posts: robinia with a diameter of 160 - 180 mm
Material cross beam: robinia with a diameter 180 - 210 mm
Width: 3.60 m
Height: 3.00 m
Safety zone: Ø8.00 m

CERTIFICATE

No. Z2 052109 0018 Rev. 00

004.416

double swing frame with A-posts for a single point swing

Connection: at the ends with steel fittings

Material posts: robinia with a diameter 150 - 180 mm

Material crossbeam: robinia with a diameter 180 - 200 mm

Length: 4.50 m

Height: 2.50 m

Safety zone: Ø8.00 m

004.417 (nest swing & 2 seat)

double swing frame with A-posts

Connection: at the ends with steel fittings

Material posts: robinia or oak poles with steel

stand with a cross section 100 x 100 mm

Material crossbeam: hot dip galvanized steel

cross section 100 x 100 mm

Length: 3.78 m

Width: 1.80 m

Height: 2.35 m

Safety zone: 8.00 x 4.00 m

**Tested
according to:**

DIN EN 1176-1:2017

DIN EN 1176-2:2017

EN 1176-1:2017

EN 1176-2:2017